

## DEKON - 35

### Specification of the tent:

- ✓ Inflatable tent, water distribution basin and easily removable built in shower
- ✓ Partition curtains for privacy and cross-contamination prevention
- ✓ Partition curtains to accomodate conveyor for immobile persons
- ✓ I would remove this as it is touched on in the first bullet
- ✓ Shower consists of two independent circuits:
  - ✓ First circuit supports decontamination system
  - ✓ Second circuit supports fresh water distribution

### Designation

### DEKON - 35

Internal useful area (m <sup>2</sup> ca.)	35
External dimensions (mm ca.)	7070 x 6000 x 3080
Internal dimensions (mm ca.)	7070 x 5250 x 2700
Packed dimensions (mm ca.)	1500 x 1100 x 1000
Weight (kg ca.)	200
Number of chambers	2
Inflation / Safety relief valve	4 / 2
Tube diameter	380 / 230



## Used materials:

**Inflatable supporting structure** - PAD textile double-sided rubber coated, high strength, abrasion resistant, airtight

**Roof** - PES textile one-sided PU coated, high strength, waterproof

**Floor** - anti-slip material

**Hygiene liner, Partition curtains:** PES textile one-sided PUR coated, waterproof

### Colours available

Tent  
Roof



Floor



Inflatable  
structure



### Technical parameters:

- ✓ Temperature range between -30 to +70 °C
- ✓ Operating pressure 0.19 - 0.23 bar

### Standard tent equipment:

- ✓ Transportation bag
- ✓ Repair kit
- ✓ Hand pump
- ✓ Set of pins, pegs, hammer and bottle adapter

### Additional tent equipment/ on request:

- ✓ Electric blower
- ✓ Heating generator
- ✓ Lighting
- ✓ Floor gates for decontamination showers and basin
- ✓ Flow water heater
- ✓ Slurry pump
- ✓ Self-priming pump
- ✓ Open, self-supporting basin
- ✓ Water tanks closed and open
- ✓ Admixing device
- ✓ Conveyor etc.

